


SERIES BS933

SUB-MINIATURE SILICON HIGH VOLTAGE RECTIFIER



PART NUMBER	PIV VOLTS	I_o AMPS @ 40° C	V_f @ I_o @ 25° C	I_r @ PIV @ 25° C	MAX SINGLE CYCLE SURGE CURRENT @ 60 Hz	T_{rr}
BS933-50	5000	.65	8	10 uA	100 AMPS	150 nSec
BS933-60	6000	.60	9	10 uA	100 AMPS	150 nSec
BS933-70	7000	.55	10	10 uA	100 AMPS	150 nSec
BS933-80	8000	.50	11	10 uA	100 AMPS	150 nSec
BS933-100	10000	.45	13	10 uA	100 AMPS	150 nSec
BS933-120	12000	.37	16	10 uA	100 AMPS	150 nSec
BS933-150	15000	.35	19	10 uA	100 AMPS	150 nSec

REVERSE RECOVERY TIME PERFORMED ON STORED CHARGE METER @ 100 mA

OPERATING TEMPERATURE, -55° C TO +150° C

STORAGE TEMPERATURE, -55° C TO +150° C

(203) 467-2591 TEL
 (203) 469-5928 FAX
 Email: Info@ edal.com
 Internet: <http://www.edal.com>

EDAL[®] INDUSTRIES
INC. SINCE 1958

51 Commerce St. East Haven, CT 06512